

Product Overview



Centrifuges & Systems



Vertical Basket Centrifuges

V 300 – 500 TP

0.14–0.50 m² filter area
3.9–31.5 L nominal volume

Key benefits:

- mobile, compact design
- easy “plug and use” installation
- ideal for scaling-up
- very simple handling
- CIP cleaning
- can be installed in separator housing/glove box



Horizontal Peeler Centrifuges

H 300 – 500 P

0.12–0.39 m² filter area
4.9–20 L nominal volume

Key benefits:

- compact design
- easy “plug and use” installation
- cGMP compliant
- fully automated operation
- ideal for scaling-up



Top Discharge Centrifuges

V 630 – 1250 TP

0.80–3.14 m² filter area
51–400 L nominal volume

Key benefits:

- flexible adaptation for moderately well filtering products
- manual discharge of filter cake
- gentle discharge, no particle damage
- automated CIP cleaning
- easy access to all product contact parts



Vertical Peeler Centrifuges

V 800 – 1250 BP

1.58–3.14 m² filter area
100–400 L nominal volume

Key benefits:

- small foot print
- cGMP compliant
- process housing opens and closes automatically
- automated product discharge
- automated CIP cleaning
- easy access to all product contact parts



Horizontal Peeler Centrifuges

H 630 – 1250 P

0.62–3.14 m² filter area
42–400 L nominal volume

Key benefits:

- wide range of applications
- meets highest cGMP standards
- fully automated and validated CIP cleaning
- all process parts accessible for inspection
- cleanroom design



Inverting Filter Centrifuges

FI – F4
HF 300.I – 1300.I

0.10–2.00 m² filter area
10–1500 kg/h capacity

Key benefits:

- for moderately well filtering products
- complete discharge
- safe discharge
- additional pressure for maximum dewatering
- centrifuge can be used for drying
- small foot print
- very simple through-the-wall installation



Vertical Basket Centrifuges

V 300 – 500 TC

0.14–0.50 m² filter area
3.9–31.5 L nominal volume

Key benefits:

- mobile, compact design
- easy “plug and use” installation
- ideal for scaling-up
- double jacket for heating and cooling
- baskets for basic filtering, sedimentation, classifying and clearing tests



Horizontal Peeler Centrifuges

H 300 – 500 PC

0.12–0.39 m² filter area
4.9–20 L nominal volume

Key benefits:

- very compact design
- choice of tabletop or portable design
- easy “plug and use” installation
- ideal for scaling-up
- fully automated operation



Vertical Peeler Centrifuges

V 800 – 1800 BC

1.58–7.07 m² filter area
100–1350 L nominal volume

Key benefits:

- excellent adaptability to changing products
- high throughputs
- separation by filtration or sedimentation
- better cake discharge due to gravity assist
- cartridge bearing and small foot print



Horizontal Peeler Centrifuges

H 630 – 1800 C

1.58–7.07 m² filter area
63–1300 L nominal volume

Key benefits:

- wide range of applications
- high batch frequency
- high washing and extraction performance
- low residual moisture levels due to high G-force
- discharge through chute or screw-conveyor
- can be used with perforated basket or back-flushing basket



Vertical Top Discharge Centrifuges

V 500 – 1250 TC

0.50–3.14 m² filter area
31.5–400 L nominal volume

Key benefits:

- flexible adaptation for difficult to filter products
- complete discharge of filter cake
- gentle discharge, no particle damage
- high washing and extraction performance
- easy to assemble
- effective system for removal of filter bag
- robust and easy system for removable border ring



Vertical Peeler Centrifuges

V 800 – 1800 BG

1.58–7.07 m² filter area
100–1350 L nominal volume

Key benefits:

- optimized application for small through large throughputs
- minimal residual moisture
- maximum reduction of chloride concentrations through optimized wash process
- available in stainless steel or rubber coated

Special Applications



Sterile Top Discharge Sedimentation Centrifuges

V 630 – 1000 TS

1.10–1.60 m² sedimentation area
100–250 L nominal volume

Key benefits:

- meets highest cGMP standards
- fully automated and validated CIP cleaning
- high G-force
- cleanroom installation



Classifying Centrifuges

630 BK II/III

0.78–0.99 m² sedimentation area
3.75–38 L nominal volume
– Titanium Dioxide production

Key benefits:

- precise separation cut
- easy adjustment of separation cut
- high throughputs
- recycling of coarse particles
- simple to install
- low maintenance, maintenance-friendly design
- TiO₂ production, Al₂O₃, SiC, CaCO₃, etc.



Vertical Dip Coating Centrifuges

V 425 TT

0.20 m² filter area
20 L nominal volume

Key benefits:

- economical coating of small parts with oil, lacquer, adhesive coatings etc.
- optimized spinning off of excess coating material
- simple to install



Vertical Multi-purpose Centrifuges

V 300 – 700 TM

0.06–0.66 m² filter area
10–150 L nominal volume

Key benefits:

- economical solution for recovering liquids and oils
- easy “plug and use” installation
- simple, robust design




Vertical Pusher Centrifuges

V 600 – 1100 P

0.4–10 long ton/h capacity

Key benefits:

- recovery of liquids and oils from chips produced by processing centers and from plastic pellets
- simple, robust design



Ball Segment Valve

BSV 150 – BSV 400

DN 150–400 nominal diameter

Key benefits:

- cGMP and FDA compliant design
- inflatable seal with large seal area; seal available in various materials
- complete, unobstructed discharge
- cavity-free aseptic design
- automated, verifiable CIP cleaning



Rebuilt Machines

Key benefits:

- international procurement
- machines from all manufacturers, assembled to suit customer requirements
- constantly changing range
- fast availability
- warranty as for a new machine
- attractive prices



Conversions/Retrofits

Key benefits:

- full mechanical overhaul
- electronic assembly upgrades
- current explosion protection regulations taken into account
- updated documentation



Drive Systems/Controls

Key benefits:

- safety checked
- modular and flexible
- standalone, or can be integrated into any DCS
- GAMP, ATEX, 21 CFR Part II, EN 12547
- remote maintenance and systems analysis
- premium component suppliers
- overall development in-house at HEINKEL

After Sales Services:

- Technical support
- Online support
- Installation and commissioning
- Preventative maintenance
- Maintenance contracts
- Spare parts logistics
- Overhauls and upgrades
- Consulting
- Training
- Rental machines
- Pilot units

HEINKEL Drying and Separation Group products are used to manufacture the following products:

- | | | |
|---|---|---|
| <ul style="list-style-type: none">• Agricultural chemicals• API (active pharmaceutical ingredients)• Aromatic substances• Biocides• Cellulose derivatives• Fragrant substances• Precious metals• Effective pigments• Electrochemical• Color pigments | <ul style="list-style-type: none">• Fine chemicals• Herbicides• Catalysts• Corrosion inhibitors• Cosmetics• Food additives and food substances• Metallic powder• Nitrocellulose• Brighteners• Pesticides• Plant extractives | <ul style="list-style-type: none">• Pharmaceutical substances• Preliminary pharmaceutical substances• Intermediate pharmaceutical products• Photographic chemicals• Specialty polymers• Vitamins |
|---|---|---|

 **CCC** COMPETENCE CENTER CENTRIFUGES



HEINKEL
Process Technology GmbH

Ferdinand-Porsche-Str. 8
74354 Besigheim
GERMANY
Telefon +49 7143 9692-0
Telefax +49 7143 9692-259
E-Mail info@heinkel.de
Internet www.heinkel.de



HEINKEL
Filtering Systems, Inc.

520 Sharptown Road
Swedesboro, NJ 08085
USA
Telefon +1 856 467-3399
Telefax +1 856 467-1010
E-Mail info@heinkelusa.com
Internet www.heinkelusa.com

 **CCC** COMPETENCE CENTER DRYERS



BOLZ
Process Technology GmbH

Sigmanner Weg 2
88239 Wangen
GERMANY
Telefon +49 7522 9162-0
Telefax +49 7522 9162-105
E-Mail info@bolz-pt.de
Internet www.heinkel.de



COMBER
Process Technology S.r.l.

Via Marconi, 13
24020 Colzate (BG)
ITALY
Telefon +39 035 737801
Telefax +39 035 737820
E-Mail salesdept@comber.it
Internet www.heinkel.de

HEINKEL
Process Technology Pte Ltd.

25 International Business Park
#4-59A German Centre
Singapore 609916
Telefon +65 6562-8048
Telefax +65 6562-8049
E-Mail info@heinkel.com.sg

HEINKEL s.r.o.

Machkova 587
500 11 Hradec Králové
CZECH REPUBLIC
Telefon +420 495 406250
Telefax +420 495 406251
E-Mail info@heinkel.cz